

Sensor-switched LED floodlight

Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661



LED

20.000 h

3000 K

3000K warm-white



38°



infrared sensor 90°



max. 10 m



Twilight switch



IP44



Light source not exchangeable



Control gear not exchangeable



2 - 1000 lux

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm	Mechanical scalability	No
With lamp	Yes, LED lamp	Reach, radial	r = 2 m (3 m ²)
With motion detector	Yes	Reach, tangential	r = 10 m (79 m ²)
Manufacturer's Warranty	3 years	Photo-cell controller	Yes
Settings via	Bluetooth	Luminous flux total product	512 lm
Version	with motion detector & Bluetooth	Measured luminous flux (360°)	512 lm
PU1, EAN	4007841058661	Total product efficiency	64,8 lm/W
Application, place	Outdoors	Colour temperature	3000 K
Application, room	outdoors, garden	Colour variation LED	SDCM5
Colour	Anthracite	Lamp	LED can be replaced
Includes corner wall mount	No	Soft light start	No
Installation site	Stand mounted	Continuous light	selectable, 4h
Installation	Stand mounted	Functions	Manual ON / ON-OFF, Timer, Master/slave override
Impact resistance	IK03	Twilight setting	2 – 2000 lx
IP-rating	IP44	Time setting	5 s – 60 Min.
Protection class	I	Basic light level function	No
Ambient temperature	-20 – 40 °C		

<https://www.steinel.de>

Subject to technical modifications

02.2023 Page 1 from 2

Sensor-switched LED floodlight

Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661




Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave modeselectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No

Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °

Detection Zone



Mögliche Montagehöhe: –
Orange: radial
Schwarz: tangential

Dimension Drawing

